



Designed with the environment in mind

Purlogix™ systems are designed to meet the criteria of the environmental and sustainability programs being implemented in today's workplace.

Our systems provide an endless, renewable supply of environmentally friendly, pure, fresh and healthy drinking water.



Our multi-stage purification process removes contaminants and delivers delicious piping hot or ice cold water through a sanitary electronic dispense port.

The sleek and stylish design fits into any office decor.

Flexible filtration options ensure that there is a Purlogix™ model to suit any requirement.

The Logical Choice!



A Purlogix™ system is the ideal addition for the office to provide a pure and healthy drinking water source.

2000e Series Features:

- Available in Black or White [PMV-2000e white only]
- Bio-Film Control in Tank [optional]
- Electronic Dispense w/Safety Hot Feature
- Ergonomic Dispense Height
- Large Dispense Area for Sports Bottles
- High Capacity Hot and Cold Tanks
- Adjustable Leveling Feet
- LED Indicator Panel
- Drip Tray with Knock-out for Drain
- Heavy Gauge Powder Coated Side Panels
- Solid State Circuit Board w/Microprocessor Control
- Adjustable Cold Control [38° to 46°]
- Sleek Appliance Appearance
- Filtered Outlet for Coffee Brewer or Accessory Item
- Leak Detection w/water Shut Off & Audio Alert [optional]

Purlogix™ is dedicated to providing customers with products that meet and exceed their expectations as well as a customer support system for total customer satisfaction.

OPTIONS

For maximum flexibility, Purlogix™ offers systems with RO, Micro Filtration or without filters. Optional In-Tank Ultraviolet [UV] Disinfection is available on all models.

MODELS		*PRV-2000e	*PMV-2000e	*PBV-2000e, PB-2000e
INPUT VOLTAGE		120V AC, 60Hz **		
POWER CONSUMPTION	COMPRESSOR	100W		
	HEATER	460W		
TANK CAPACITY	COLD	1.3 Gallons with 0.8 Gallons Chilled		
	HOT	0.8 Gallons		
FILTRATION SYSTEMS		80 GPD Reverse Osmosis	Sediment & Carbon MF	No System Installed
DIMENSIONS		11.8"W x 16.5"D x 49.2"H		
WEIGHT		77 lbs.	75 lbs.	73 lbs.

*Includes In-Tank UV * *Systems also available in 220V 50Hz

The Logical Choice!